





# CKS-40

## SURFACE TYPE

LED Self-Contained Emergency  
Keluar Sign



### Dimensions



### Technical Information

Mode of Operation :	Maintained
Input Voltage :	240V $\pm$ 10%, 50/60Hz
Battery Type :	3.6V, 2200mAh, 4.8Wh Environment Friendly Lithium-ion Battery
Lamp Type :	40pcs x 0.1W LED Class 1, ta-35°C
Operation Temperature :	0°C to 60°C
Charger :	Constant Current
Indication Type :	Red LED "On" Indicates Charging Mode. Push Test-Switch to Simulate Power Failure.
Backup Duration :	3 Hours
Fitting Construction :	Electro-Galvanized Sheet Steel Casing with Epoxy Powder Coated
Weight :	$\pm$ 2.0kg
Warranty :	Component - 5 Years Battery - 1 Year <i>(Terms &amp; Condition Apply)</i>
Certified Compliance :	Malaysia Standards MS-983:2004, MS-619-2-22:2005,
Certified By :	MS IEC 60598-1:2012, IP20 SIRIM QAS International Sdn. Bhd. Jabatan Bomba dan Penyelamat Malaysia
Application :	Surface Wall Mounting
Dimension :	in mm
Tolerance :	$\pm$ 0.03mm