

WELUX LED Downlights

Platin Comfort Series

Housing and Trim: Die-cast aluminium
 Mounting type: Recess
 Heat Management: Die-cast aluminium heat sink
 Reflector: Aluminium
 Diffuser: Clear glass or Frosted Glass

LED Modules
 GERMAN Technology
 Comfort COB - Up to 1800lm
 Long service life time : 50,000 hours (L80/B10)
 Ambient temperature - 40°C to +40°C

Drivers: 150mA / 250mA / 300mA / 350mA
 (optional: Dimmable available)
 Power factor at full load : 0.97
 SELV , Low Ripple current < 1% ,THD <15%
 Warranty: 5 years

Standards
 EN 620301: LED modules for general lighting - Safety specification
 EN 62471: Photobiological safety of lamps and systems
 EN 55015: Radio disturbance emissions
 EN 61000-3-2 Limited for harmonic emissions
 EN 61547: Immunity requirements

Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Luminous Flux (Lm)	Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension (Dia x H) mm	Dimension (Cut out) mm
P4-3-4W-IP65 P5-3-4W-IP65	4.2W	220-240	50/60Hz	0.95	Warm white	2700K	615	148	40	>82	A+	110 x 59 110 x 110 x 59	90 90 x 90
		220-240	50/60Hz	0.95	Warm white	3000K	645	155	40	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	665	160	40	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	670	161	40	>82	A+		
P4-3-7W-IP65 P5-3-7W-IP65	7.3W	220-240	50/60Hz	0.95	Warm white	2700K	965	133	70	>82	A+	110 x 59 110 x 110 x 59	90 90 x 90
		220-240	50/60Hz	0.95	Warm white	3000K	1015	140	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	1045	144	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	1055	145	70	>82	A+		
P4-4-10W-IP65 P5-4-10W-IP65	10.3W	220-240	50/60Hz	0.95	Warm white	2700K	1505	146	70	>82	A+	127 x 70 127 x 127 x 70	110 110 x 110
		220-240	50/60Hz	0.95	Warm white	3000K	1585	154	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	1630	158	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	1645	160	70	>82	A+		
P4-4-12W-IP65 P5-4-12W-IP65	12.2W	220-240	50/60Hz	0.95	Warm white	2700K	1720	141	70	>82	A+	127 x 70 127 x 127 x 70	110 110 x 110
		220-240	50/60Hz	0.95	Warm white	3000K	1810	149	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	1865	153	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	1885	155	70	>82	A+		

*Colour tolerance: 3 MacAdam **Production tolerance of luminous flux and efficiency: ±10% ***Min. CRI ±3% ****Power consumption: ±10%
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.

WELUX LED Downlights

Platin Comfort Series

Housing and Trim: Die-cast aluminium
 Mounting type: Recess
 Heat Management: Die-cast aluminium heat sink
 Reflector: Aluminium
 Diffuser: Clear glass or Frosted Glass

LED Modules
 GERMAN Technology
 Comfort COB - Up to 3800lm
 Long service life time : 50,000 hours (L80/B10)
 Ambient temperature - 40°C to +40°C

Drivers: 400mA / 500mA / 600mA / 700mA
 (optional: Dimmable available)
 Power factor at full load : 0.97
 SELV , Low Ripple current < 1% ,THD <15%
 Warranty: 5 years

Standards
 EN 620301: LED modules for general lighting - Safety specification
 EN 62471: Photobiological safety of lamps and systems
 EN 55015: Radio disturbance emissions
 EN 61000-3-2 Limited for harmonic emissions
 EN 61547: Immunity requirements



Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Luminous Flux (Lm)	Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension (Dia x H) mm	Dimension (Cut out) mm
P4-4-14W-IP65 P5-4-14W-IP65	14.1W	220-240	50/60Hz	0.95	Warm white	2700K	1930	137	70	>82	A+	127 x 70 127 x 127 x 70	110 110 x 110
		220-240	50/60Hz	0.95	Warm white	3000K	2030	144	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	2090	148	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	2110	149	70	>82	A+		
P4-4-17W-IP65 P5-4-17W-IP65	17.3W	220-240	50/60Hz	0.95	Warm white	2700K	2585	149	70	>82	A+	127 x 70 127 x 127 x 70	110 110 x 110
		220-240	50/60Hz	0.95	Warm white	3000K	2725	158	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	2805	162	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	2860	165	70	>82	A+		
P4-6-21W-IP65 P5-6-21W-IP65	21.2W	220-240	50/60Hz	0.95	Warm white	2700K	3030	143	70	>82	A+	165 x 81 165 x 165 x 81	145 145 x 145
		220-240	50/60Hz	0.95	Warm white	3000K	3185	151	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	3280	155	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	3345	158	70	>82	A+		
P4-6-25W-IP65 P5-6-25W-IP65	25.1W	220-240	50/60Hz	0.95	Warm white	2700K	3445	137	70	>82	A+	165 x 81 165 x 165 x 81	145 145 x 145
		220-240	50/60Hz	0.95	Warm white	3000K	3625	144	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	3730	148	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	3805	151	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	3765	150	70	>82	A+		

*Colour tolerance: 3 MacAdam **Production tolerance of luminous flux and efficiency: ±10% ***Min. CRI ±3% ****Power consumption: ±10%
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.

WELUX LED Downlights

Platin Comfort Series

Housing and Trim: Die-cast aluminium
 Mounting type: Recess
 Heat Management: Die-cast aluminium heat sink
 Reflector: Aluminium
 Diffuser: Clear glass or Frosted Glass

LED Modules
 GERMAN Technology
 Comfort COB - Up to 5500lm
 Long service life time : 50,000 hours (L80/B10)
 Ambient temperature - 40°C to +40°C

Drivers: 900mA / 1050mA / 1100mA / 1200mA
 (optional: Dimmable available)
 Power factor at full load : 0.97
 SELV , Low Ripple current < 1% ,THD <15%
 Warranty: 5 years

Standards
 EN 620301: LED modules for general lighting - Safety specification
 EN 62471: Photobiological safety of lamps and systems
 EN 55015: Radio disturbance emissions
 EN 61000-3-2 Limited for harmonic emissions
 EN 61547: Immunity requirements



Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Luminous Flux (Lm)	Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension (Dia x H) mm	Dimension (Cut out) mm
P4-8-32W-IP65 P5-8-32W-IP65	32.0W	220-240	50/60Hz	0.95	Warm white	2700K	4455	139	70	>82	A+	220 x 90 220 x 220 x 90	200 200 x 200
		220-240	50/60Hz	0.95	Warm white	3000K	4690	147	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	4830	151	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	4920	154	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	4875	152	70	>82	A+		
P4-8-38W-IP65 P5-8-38W-IP65	38.0W	220-240	50/60Hz	0.95	Warm white	2700K	5045	133	70	>82	A+	220 x 90 220 x 220 x 90	200 200 x 200
		220-240	50/60Hz	0.95	Warm white	3000K	5310	140	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	5465	144	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	5575	147	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	5520	145	70	>82	A+		
P4-8-40W-IP65 P5-8-40W-IP65	40.1W	220-240	50/60Hz	0.95	Warm white	2700K	5230	130	70	>82	A+	220 x 90 220 x 220 x 90	200 200 x 200
		220-240	50/60Hz	0.95	Warm white	3000K	5505	137	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	5670	141	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	5780	144	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	5725	143	70	>82	A+		
P4-8-44W-IP65 P5-8-44W-IP65	44.2W	220-240	50/60Hz	0.95	Warm white	2700K	5590	127	70	>82	A+	220 x 90 220 x 220 x 90	200 200 x 200
		220-240	50/60Hz	0.95	Warm white	3000K	5885	133	70	>82	A+		
		220-240	50/60Hz	0.95	Neutral white	4000K	6060	137	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5000K	6175	140	70	>82	A+		
		220-240	50/60Hz	0.95	Cool white	5700K	6120	139	70	>82	A+		

*Colour tolerance: 3 MacAdam **Production tolerance of luminous flux and efficiency: ±10% ***Min. CRI ±3% ****Power consumption: ±10%
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.